


# METHOD AND DEVICE FOR ENCODING IMAGE

Patent number: JP6292188  
Publication date: 1994-10-18  
Inventor: FUKUDA HIDEKI; HONJO MASAHIRO; EGAWA TADASHI  
Applicant: MATSUSHITA ELECTRIC IND CO LTD  
Classification:  
- International: H04N7/137; G06F15/66; H04N11/04  
- european: G06T9/00P  
Application number: JP19920008976 19920122  
Priority number(s): JP19920008976 19920122

Report a data error here

## Abstract of JP6292188

**PURPOSE:** To eliminate a coding noise due to a mobile body and to perform image coding with high efficiency by selecting a predictive reference image in which the pattern of a coding object block in a coding object image exists adaptively. **CONSTITUTION:** A pattern detector 1 detects the fact that the pattern of the coding object block exists in a front reference image or rear reference image, and outputs it as a pattern control signal. A first selector 2 selects either or whole front predictive error signal train, rear predictive error signal train and an interpolation predictive error signal train by the pattern control signal. A coding distortion decision device 3 outputs a signal train in which the minimum coding distortion can be obtained with prescribed quantity of codes in an input signal train as a distortion decision control signal, and a second selector 4 selects the signal train in which the minimum coding distortion can be obtained with the prescribed quantity of codes by the signal.



Data supplied from the esp@cenet database - Worldwide